



SPECIFICATION SHEET

“4010” NM

Nonmetallic Thread Compound for Rotary Shouldered & Premium Self-Sealing Casing/Tubing Connections

COLOR	Gray
PENETRATION	300 – 330 (ASTM D 217)
WEIGHT/GALLON	10.4 pounds/gallon
DROPPING POINT	550 °F/288 °C (typ)
FLASH POINT	396 °F/202 °C (min)
BRUSHABLE TO	-40 °F/-40 °C
FRICTION (TORQUE) FACTOR	1.0 (per API RP 7A1)* ⁽¹⁾
SALT SPRAY	1500 hrs. min (ASTM B117)
CONTAINS	Graphite, nonmetallic additives

Bestolife 4010 NM is the fourth generation of the highly successful Bestolife family of compounds designed and developed to address the environmental concerns, related to the use of thread compounds for rotary shouldered and premium connections, in ecologically sensitive areas of the world, such as the North Sea, Nova Scotia, Newfoundland, the South Atlantic, Alaska, and Sakhalin Island.

Bestolife 4010 NM combines the excellent low temperature application properties of Bestolife 3010 Ultra with superior downhole galling resistance and enhanced ecotoxicological properties to provide the ideal drill-string solution for all rotary shouldered (drill pipe/tool joints/drill collars) and many proprietary premium self-sealing casing/tubing connection applications, irrespective of offshore drilling location.

- ✓ Applies easily to cold wet connections exposed to seawater in ambient temperatures as low as -40 °F/-40 °C and yet provides optimum protection in the deepest, hottest holes. Will provide lubrication and protection to 600 °F/316 °C and the solids will protect to 1,000 °F/538 °C.
- ✓ Has the ability to prevent galling of contact surfaces (including non-magnetic materials) under high bearing loads and to form a continuous gasket between the shoulders of a rotary connection during make-up. This is achieved through the innovative combination of graphite and other non-toxic materials, which interact to form a seal when compressed between seals, threads, and shoulders during make-up to provide performance properties which are equal to the very best heavy metal compounds. This gasket-like seal prevents connection wash-out, even under high internal fluid pressures and the combined loading of directional drilling, to provide maximum protection in the toughest conditions.
- ✓ Conforms with ISO/DIS 13678 and API RP 5A3
- ✓ Provides superior protection for the threaded connections of OCTG's during transit and long term storage.
- ✓ Meets the current (2007) OSPAR Commission Harmonised Mandatory Control Scheme (HOCNF) regulations for the protection of the marine environment of the North-East Atlantic/North Sea. Will be registered for use in the UK/Netherlands as an OCNS Category E Chemical and in Norway/Denmark as a Color Category Yellow Pipe Dope.

*⁽¹⁾ API RP 7A1: “Recommended Practice for Testing of Thread Compound for Rotary Shouldered Connections”
NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

**A MATERIAL SAFETY DATA SHEET IS AVAILABLE FROM THE MANUFACTURER.
DO NOT USE ON OXYGEN LINES OR IN OXYGEN ENRICHED ATMOSPHERES.**